



ODM Wire Electrical Copper Connector Terminal Lug

Our Product Introduction

Basic Information

- Place of Origin: china
- Brand Name: jinshunlai
- Certification: ISO, AISI, ASTM, GB, EN, DIN
- Model Number: 0.1mm-900mm
- Minimum Order Quantity: 1kg
- Price: Contact Us
- Packaging Details: Waterproof Paper, Steel Strip Packed and other Standard Export Seaworthy Package, or customized package
- Delivery Time: 5day
- Payment Terms: L/C, T/T , Western Union
- Supply Ability: 90000ton



Product Specification

- Chemical Composition: Cu-Ni
- Corrosion Resistance: Excellent
- Density: 8.9 G/cm3
- Electrical Conductivity: $\leq 20\%$ IACS
- Elongation: 30-40%
- Formability: Good
- Hardness: High
- Heat Treatment: Annealing
- Machinability: Good
- Melting Point: 1453-1475°C
- Name: Copper Connector
- Tensile Strength: 400-550 MPa
- Thermal Conductivity: 50-70 W/mK
- Weldability: Good
- Yield Strength: 200-350 MPa



More Images



for more products please visit us on copper-solid.com

Product Description

ODM Wire Electrical Copper Connector Terminal Lug

Application

Terminal connectors are used to connect tap conductor to power equipments (transformer,circuit breaker,disconnect switch.etc)or to wall bushing of substation.Aluminum connectors are Also used to connect the tap conductor of T-connector.The connectors inclede compressive-type and bolted,both types have angle of 0°, 30° and 90°with the direction of tap conductor.

Specification

Product name	DTL Bimetal Cable Lugs
Color	AS Picture
Delivery time	Quantity
Usage	Accessories
OEM/ODM	Customization Service Provided



Wuxi Jinnuo copper Co.,Ltd



+86-17763564398



sales01@shuangheyisteel.com



copper-solid.com

32 Chengnan Road, New District, Wuxi City, Jiangsu Province, China